

Oswal[®]
ALWAYS AHEAD IN QUALITY



Professional P.A. & D. J. System

TWO ZONE POWER BOOSTER AMPLIFIER

OPA-3K



1100+1100 WATTS RMS. at 10% THD.

- AC 230V + 10%, Forced Cooling.
- 50-15000 Hz+3dB, S /N R - 60dB.
- 4 Ohms Direct Out For Speaker Channel A-B.

OPA-2K



840+840 WATTS RMS. at 10% THD.

- AC 220V + 10%, Forced Cooling.
- 50-15000 Hz+3dB, S /N R - 60dB.
- 4 Ohms Direct Out For Speaker Channel A-B.

TWO ZONE P.A. AMPLIFIER

TZA-5000U



250+250 WATT. RMS. at 10% THD.
USB,SD/MP3 DIGITAL PLAYER

- AC 230V & 24V DC Operation, Bass, Treble, Master Control.
- 6 Mic 0.6mV/4.7KW, 2 AUX-100mV, Stereo input L/R.
- 200mV/100KW, 4Ω, 8Ω & 70V-100V Line Matching.

TZA-4000U



200+200 WATT. RMS. at 10% THD.
USB,SD/MP3 DIGITAL PLAYER

- AC 230V & 24V DC Operation, Bass, Treble, Master Control.
- 6 Mic 0.6mV/4.7KW, 2 AUX-100mV, Stereo input L/R.
- 200mV/100KW, 4Ω, 8Ω & 70V-100V Line Matching.

SUPER POWER P.A. & BOOSTER AMPLIFIER

PRO-12000M



1200 WATT. RMS. at 10% THD.

- AC 230V Operation, Bass, Treble, Mid, 1V/200mV Line Out
- 2Ω, 4Ω & 70V-100V Line Matching, Force cooling.
- 1V/200mV Line in with Selector Switch.

SSA-5000DP



500 WATT. RMS. at 10% THD.

- AC 230V & 36V DC Operation, 7 Mic & 2 AUX input.
- Bass, Treble, Master Control.
- 4Ω, 8Ω & 70V-100V Line Matching.

DJ SERIES POWER BOOSTER AMPLIFIER

PBT-701U



700 WATT. RMS. at 10% THD.
USB,SD/MP3 DIGITAL PLAYER

- AC 230V Operation, Bass, Treble, Mid, 1V/200mV Line Out
- 2Ω, 4Ω & 70V-100V Line Matching, Force cooling.
- 1V/200mV Line in with Selector Switch, with USB.

PBT-701



700 WATT. RMS. at 10% THD.

- AC 230V Operation, Bass, Treble, Mid, 1V/200mV Line Out
- 2Ω, 4Ω & 70V-100V Line Matching, Force cooling.
- 1V/200mV Line in with Selector Switch.

PBT-606



600 WATT. RMS. AT 10% THD.

- AC 230V Operation, Bass, Treble, Mid, 1V/200mV Line Out
- 2Ω, 4Ω & 70V-100V Line Matching, Force cooling.
- 1V/200mV Line in with Selector Switch.

HIGH POWER AMPLIFIER

SSA-300U



300 WATT. RMS. at 10% THD.
USB,SD/MP3 DIGITAL PLAYER

- AC 230V & 24V DC Operation, 6 Mic & 2 Aux. Input.
- 4Ω, 8Ω & 70V-100V Line Matching, With USB.
- 1V Line, Pre out 200mV Bass, Treble, Master Control.

SSA-250U



250 WATT. RMS. at 10% THD.
USB,SD/MP3 DIGITAL PLAYER

- AC 230V & 24V DC Operation, 6 Mic & 2 Aux. Input.
- 4Ω, 8Ω & 70V-100V Line Matching, With USB.
- 1V Line, Pre out 200mV Bass, Treble, Master Control.

SSA-250



250 WATT. RMS. at 10% THD.

- AC 230V & 24V DC Operation, 6 Mic & 2 Aux. Input.
- 4Ω, 8Ω & 70V-100V Line Matching.
- 1V Line, Pre out 200mV Bass, Treble, Master Control.

HIGH POWER AMPLIFIER

SSA-160U



**160 WATTS. RMS. at 10% THD.
USB,SD/MP3 DIGITAL PLAYER**

- AC 230V & 24V DC Operation, 5 Mic & 2 Aux input.
- 4Ω, 8Ω & 70V-100V Line Matching, With USB.
- 1V Line, Pre out 200mV, Bass, Treble, Master Control.

SSA-100UE



**100 WATTS. RMS. at 10% THD.
USB,SD/MP3 DIGITAL PLAYER WITH ECHO.**

- AC 230V & 12V DC Operation, 5 Mic & 2 Aux. Input.
- 4Ω, 8Ω, 16Ω & 70V-100V Line Matching, With USB
- Pre out 200mV, Bass, Treble, Master Control, With Echo.

SSA-120UE



**120 WATTS. RMS. at 10% THD.
USB,SD/MP3 DIGITAL PLAYER WITH ECHO.**

- AC 230V & 12V DC Operation, 5 Mic & 2 Aux. Input.
- 4Ω, 8Ω, 16Ω & 70V-100V Line Matching, With USB
- Pre out 200mV, Bass, Treble, Cut Type, With Echo.

SSA-100U



**100 WATTS. RMS. at 10% THD.
USB,SD/MP3 DIGITAL PLAYER**

- AC 230V & 12V DC Operation, 5 Mic & 1 Aux. Input.
- 4Ω, 8Ω, 16Ω & 70V-100V Line Matching, With USB
- Pre out 200mV, Bass, Treble, Master Control.

SSA-120U



**120 WATTS. RMS. at 10% THD.
USB,SD/MP3 DIGITAL PLAYER**

- AC 230V & 12V DC Operation, 5 Mic & 2 Aux. Input.
- 4Ω, 8Ω, 16Ω & 70V-100V Line Matching, With USB
- Pre out 200mV Bass, Treble, Cut Type.

SSA-80U



**80 WATTS. RMS. at 10% THD.
USB,SD/MP3 DIGITAL PLAYER**

- AC 230V & 12V DC Operation, 5 Mic & 1 Aux. Input.
- 4Ω, 8Ω, 16Ω & Matching, With USB
- Pre out 200mV, Bass, Treble, Master Control.

POWER AMPLIFIER

SSA-60U



**60 WATTS. RMS. at 10% THD.
USB,SD/MP3 DIGITAL PLAYER**

- AC 230V & 12V DC Operation, 3 Mic & 1 Aux. Input.
- 4Ω, 8Ω, 16Ω & 100V Line Matching, With USB
- Speaker Output, Bass, Treble Control.

SSA-60UC



**50 WATTS. RMS. at 10% THD.
USB,SD/MP3 DIGITAL PLAYER**

- AC 230V & 12V DC Operation, 3 Mic & 1 Aux. Input.
- 4Ω, 8Ω, 16Ω & 100V Line Matching, With USB
- Speaker Output, Bass, Treble Control.

SSA-25U



**25 WATTS. RMS. at 10% THD.
USB,SD/MP3 DIGITAL PLAYER**

- AC 230V & 12V DC Operation, 2 Mic.
- Speaker Output, 4Ω, 8Ω, 16Ω
- Tone Control, With USB Reader.

DVD PLAYER WITH AMPLIFIER

ODA-1200



**120 WATTS. RMS. at 10% THD.
USB,SD/MP3 DIGITAL PLAYER**

- ACD/VCD/DVD/MP3/MP4/USB Playback, 4Ω,8Ω,16Ω.
- AC 230V & 12V DC Operating, & 100V Line Matching.
- 5 Mic & 1 Aux Input, Bass Treble & Master Control.

ODA-850



**85 WATTS. RMS. at 10% THD.
USB,SD/MP3 DIGITAL PLAYER**

- ACD/VCD/DVD/MP3/MP4/USB Playback, 4Ω,8Ω,16Ω.
- AC 230V & 12V DC Operating, & 100V Line Matching.
- 4 Mic & 1 Aux Input, Bass Treble & Master Control.

ODA-600



**60 WATTS. RMS. at 10% THD.
USB,SD/MP3 DIGITAL PLAYER**

- ACD/VCD/DVD/MP3/MP4/USB Playback, 4Ω,8Ω,16Ω.
- AC 230V & 12V DC Operating, & 100V Line Matching.
- 3 Mic & 1 Aux Input, Bass Treble & Master Control.

PROFESSIONAL DVD PLAYERS WITH USB

CDJ-700



**ANTI-SHOCK DVD PLAYER
USB,SD/MP3 DIGITAL PLAYER**

- ACD/VCD/DVD/MP3/MP4/USB Playback.
- AC 230V & 12V DC Operating.
- Headphone with Volume, L/R Channel Volume.
- 200mv & 1V Mono Output for D.J. Booster Amplifier & Mixer.

PRE-AMPLIFIER USB READER

OP-96



20 WATTS. RMS. at 10% THD.

- Pre. Amp., with Recoder & Speaker.
- 12V Car Battery Operation.
- 1Mic, 1 Aux Input.

OP-AUX



USB,SD/MP3 DIGITAL PLAYER

- 12V Car Battery Operation.
- With USB Input.

DIGITAL ECHO & REVERB

ODJ-77



- AC 230V & 12V DC Operation.
- 4 Mic Input.
- Echo Delay with Extra Long Delay Time.

ODC-40



- AC 230V & 12V DC Operation.
- 4 Mic Input.
- Echo Delay with Extra Long Delay Time.

ODC-8000



- AC 230V & 12V DC Operation.
- 2 Mic Input.
- Option to Operate direct Mic/Mixer.
- 5 Mode Digital Echo & Reverb.

DISTRIBUTOR AMPLIFIER

ODC-20



- 230V AC Operation.
- Drive 10 Stereo Amplifiers or 20 Mono Amplifiers.
- Input Attenuate Control for Left & Right.

PROFESSIONAL D. J. MIXER WITH BUILT IN USB PLAYER

ODM-300U



USB,SD/MP3 DIGITAL PLAYER

- AC 230V, 3 Channels, Headphone with Volume.
- Gain, Bass, Treble, Mid, With USB Reader.

DIGITAL ECHO MIXER WITH SLIDE CONTROL

OM-666



STEREO AUDIO MIXER WITH USB

- AC/DC 12V Operation, 6 Channels.
- Bass, Treble, Pan & with USB Reader.
- Echo effect for each Channel, L/R Output.

OM-999



STEREO AUDIO MIXER WITH USB

- AC/DC 12V Operation, 9 Channels.
- Bass, Treble, Pan & with USB Reader.
- Echo effect for each Channel, L/R Output.

PROFESSIONAL AUDIO MIXER

SM-6



DIGITAL ECHO MIXER

- AC 230V, 6 Channels, 2 Outputs.
- Headphone with Volume.
- Gain, Bass, Treble, Mid.

USM-6



DIGITAL ECHO MIXER WITH USB

- AC 230V, 6 Channels, 2 Outputs.
- Headphone with Volume.
- Gain, Bass, Treble, Mid, With USB Reader.

USM-8



DIGITAL ECHO MIXER WITH USB

- AC 230V, 8 Channels, 2 Outputs.
- Headphone with Volume.
- Gain, Bass, Treble, Mid, With USB Reader.

P.A. FULL RANGE SPEAKERS

OS 18 RC-1000



- Frame : AL, 18"
- Cone : Paper Cone Cloth Edge
- Impedance : 8 Ohms
- Max Power : 2500 PMPO
- Magnet Size : 280 x 110 x 25

OS 15 RC-1000



- Frame : AL 15"
- Cone : Paper Cone Cloth Edge
- Impedance : 8 Ohms
- Max Power : 2200 PMPO
- Magnet Size : 280 x 80 x 20

OS 18 MB-1000 P



- Frame : AL/CAP 18"
- Cone : Paper Cone Cloth Edge
- Impedance : 8 Ohms
- Max Power : 2500 PMPO
- Magnet Size : 280 x 110 x 25

OS 15 RC-700



- Frame : MS 15"
- Cone : Paper Cone Cloth Edge
- Impedance : 8 Ohms
- Max Power : 2200 PMPO
- Magnet Size : 220 x 80 x 20

OS 18 RC-700



- Frame : AL, 18"
- Cone : Paper Cone Cloth Edge
- Impedance : 8 Ohms
- Max Power : 2200 PMPO
- Magnet Size : 220 x 110 x 25

OS 15 MB-400 P



- Frame : AL 15"
- Cone : Paper Cone Cloth Edge
- Impedance : 8 Ohms
- Max Power : 2200 PMPO
- Magnet Size : 180 x 80 x 20

P.A. FULL RANGE SPEAKERS

OS 15 BM-400 (J)



- Frame : AL 15"
- Cone : Paper Cone Cloth Edge
- Impedance : 8 Ohms
- Max Power : 2200 PMPO
- Magnet Size : 180 x 80 x 20

OS 12 MB-250



- Frame : AL 12"
- Cone : Paper Cone Cloth Edge
- Impedance : 8 Ohms
- Max Power : 2000 PMPO
- Magnet Size : 155 x 57 x 20

OS 15 MB-300



- Frame : AL 15"
- Cone : Paper Cone Cloth Edge
- Impedance : 8 Ohms
- Max Power : 2200 PMPO
- Magnet Size : 180 x 80 x 20

OS 12 MB-200



- Frame : MS 12"
- Cone : Paper Cone Cloth Edge
- Impedance : 8 Ohms
- Max Power : 2000 PMPO
- Magnet Size : 155 x 57 x 20

OS 15 FT-200



- Frame : MS 15"
- Cone : Paper Cone Cloth Edge
- Impedance : 8 Ohms
- Max Power : 2000 PMPO
- Magnet Size : 155 x 57 x 20

OS 12 FX-100



- Frame : MS 12"
- Cone : Paper Cone Cloth Edge
- Impedance : 8 Ohms
- Max Power : 1500 PMPO
- Magnet Size : 135 x 57 x 20

P.A. & D.J. COLUMNS

OS-828



SPEAKER 18" X 2

- Power Rating : 2400W/5000W
- Frequency Response : 25Hz-900Hz
- Nominal Impedance : 4 Ohms

OS-818



SPEAKER 18" X 1

- Power Rating : 1200W/2500W
- Frequency Response : 30Hz-900Hz
- Nominal Impedance : 8 Ohms

OS-825



SPEAKER 15" X 2

- Power Rating : 1600W/3200W
- Frequency Response : 35Hz-18Khz
- Nominal Impedance : 4 Ohms

OS-815



SPEAKER 15" X 1

- Power Rating : 800W/1600W
- Frequency Response : 35Hz-18Khz
- Nominal Impedance : 8 Ohms

OS-725



SPEAKER 15" X 2

- Power Rating : 1200W/2800W
- Frequency Response : 35Hz-18Khz
- Nominal Impedance : 4 Ohms

P.A. & D.J. COLUMNS

OS-728



SPEAKER 18" X 2

- Power Rating : 2000W/5000W
- Frequency Response : 25Hz-900Hz
- Nominal Impedance : 4 Ohms

OS-718



SPEAKER 18" X 2

- Power Rating : 1000W/2500W
- Frequency Response : 30Hz-900Hz
- Nominal Impedance : 8 Ohms

OS-722



SPEAKER 12" X 2

- Power Rating : 200W/600W
- Frequency Response : 50Hz-15Khz
- Nominal Impedance : 16 Ohms

OS-715



SPEAKER 15" X 1

- Power Rating : 600W/1500W
- Frequency Response : 35Hz-18Khz
- Nominal Impedance : 8 Ohms

OS-712



SPEAKER 12" X 1

- Power Rating : 100W/300W
- Frequency Response : 50Hz-15Khz
- Nominal Impedance : 8 Ohms

UNIT HORN COMBINATION

OTH-40



Output : 40 Watts
Impedance : 8 Ohms

OTH-20



Output : 25 Watts
Impedance : 8 Ohms

MEGA PHONE

OMP-20



- Output : 20 Watts
- Power Source : 7.5V (5x UM-1 Cells)

TRUMPET HORN

OTH-18"/20"/22"/24"



REFLEX HORN

ORH-18"/21"



HANGING MICROPHONE

OSM-6

OSM-4



P.A. METAL COLUMNS

OS-30 T



- Input Power: 30 Watts.
- Imped. : 16 Ohms 100V LMT.
- Tape : 30W, 20W, 10W
- Nos. of Speakers : 4

OS-20 T



- Input Power: 20 Watts.
- Imped. : 8 Ohms 100V LMT.
- Tape : 20W, 15W, 10W
- Nos. of Speakers : 2

OS-10 T



- Input Power: 7.5 Watts.
- Imped. : 4 Ohms 100V LMT.
- Tape : 7.5W, 5W, 2.5W
- Nos. of Speakers : 1

DRIVER UNITS

ODU-40



- Input Power :
40 Watts RMS / 50 Watts Max.
- Impedance / Power Taps :
16 Ohms.

ODU-55



- Input Power :
55 Watts RMS / 60 Watts Max.
- Impedance / Power Taps :
16 Ohms.

ODU-60



- Input Power :
60 Watts RMS / 65 Watts Max.
- Impedance / Power Taps :
16 Ohms.

ODU-80



- Input Power :
80 Watts RMS / 90 Watts Max.
- Impedance / Power Taps :
16 Ohms.

ODU-100



- Input Power :
100 Watts RMS / 120 Watts Max.
- Impedance / Power Taps :
16 Ohms.

ODU-60 XT



- Input Power :
65 Watts RMS / 70 Watts Max.
- Impedance / Power Taps :
100v Line 60/50/40/30/20/10 Watts.

P.A. CUBE

OC-28



OC-30



30 WATTS. RMS WITH 8" DUAL CONE SPEAKER

- AC 230V & 12V DC built in Maintenance free Battery .
- Auto Change over & Rechargeable Battery.
- Effects: Digital Vocal Echo (Mic-1).
- 3 Mic Low Impedance/1 Aux.-USB Player.
- Compact size, Moulded Grill & Plywood Rexine finished.
- Line out & External Speaker out (Switchable).
- Built in USB Player with Remote.

SNAKE CABLE & ACCESSORY

DD3-ADAPTOR



SNAKE CABLE



- 2 Core, 4 Core, 8 Core, 10 Core.
- 12 Core, 16 Core, 24 Core, 32 Core.

UNIT DIAPHRAGM



- REGULAR, DLX, AL FOIL & LMT (DU / TOA)

ROUND & SQUARE COLUMN SOCKETS



MULTI JECK BOX



SNAKE CABLE



- 2 Core, 4 Core, 8 Core, 10 Core.
- 12 Core, 16 Core, 24 Core, 32 Core.

METAL GULLA



STAND CHUTKI



LINE MATCHING TRANSFORMERS



MICROPHONE STANDS, SPEAKERS & LIGHT STANDS



R.B.F. DX.F. EX.HX. GSF-90 BOOM FLOOR

• Height :	61"	61"	62"	61"	90"
• Base Dia :	10"	10"	12"	Tripod	Tripod
• Weight :	3.150	4.400	4.800	2.700	3.000



Desk Stand Casting R.B.F. DX.Table GST-90

• Height :	61"	61"	62"	61"
• Base Dia :	10"	10"	12"	Tripod
• Weight :	3.150	4.400	4.800	2.700



CBS 102

- Height : 72".
- Base Dia : Tripod
- Weight : 11.000

CBS 103

- Height : 72".
- Base Dia : Tripod
- Weight : 10.000

CBS 104

- Height : 60".
- Base Dia : Tripod
- Weight : 9.000

LS 801

- Height : 8".
- Base Dia : Tripod
- Weight : 11.000

LS-802

- Height : 8".
- Base Dia : Tripod
- Weight : 11.000

LS 1201


- Height : 12".
- Base Dia : Tripod
- Weight : 15.000

CROSSOVER NETWORKS PLATE


ONP-20



ONP-26



ONP-450



ONP-750



ONP-PHT




ONP-450 (I)




ONP-750 (I)



ONP-600x450



ONP-1200x750



ONP-600X450(A)



MIKE WIRE SHIELDED



MIK WIRE

- 40/40 SINGLE CORE.
- 19/40 TWO CORE.
- 19/38 TWO CORE.
- 19/38 TC/BC.

TWIN PARALLEL WIRE SHIELDED



SPEAKER WIRE

- 40/25 TC/BC.
- 23/36 TC/BC.
- 40/36 TC/BC.
- 100/40 (Round 2 core/4 core).
- 70/76(Round 2 core/4 core).
- 100/76 (Round 2 core/4 core).

MONO TO XLR & XLR TO XLR (CABLE)



LEAD SIZE

- 5 MTR.
- 10 MTR.
- 15 MTR.
- 20 MTR.

CONNECTOR LEAD FOR ALL PLUG-INS



AMPLIFIERS DRIVER UNITS MIXERS SPEAKERS ACCESSORIES

Oswal[®]
ALWAYS AHEAD IN QUALITY



Distributor / Dealer